

## Rockfon Artic®

**0.75**  
NRC

### Features & Benefits

- Smooth white surface
- Economic solution with standard sound absorption (NRC = 0.75)
- High fire performance
- Lightweight panel, easy to carry and install
- Available in square lay-in and tegular

### Applications

- Department stores
- Corridor



Rockfon ceiling tiles are manufactured using advanced stone wool technology. All stone wool tiles benefit from:



**High Acoustic Absorption**



**Class A Fire Rated Performance**



**Moisture and Sag Resistance**



**Smooth, Modern Aesthetics**

# Rockfon Artic®

## LEED® v4 Highlights

### Materials and Resources (MR)

- Waste Management Planning
- Interiors Life Cycle Impact Reduction
- Environmental Product Declarations
- Sourcing of Raw Materials
- Material Ingredients
- Waste Management

### Indoor Environmental Quality (EQ)

- Low-Emitting Materials ✓
- ✓ Interior Lighting ✓
- ✓ Acoustic Performance ✓

**Recycled Content:** up to 37%



Edge designation	Item number	Modular size (nominal)	lbs/sqft	sqft/carton	NRC	AC	Fire Class	Light Reflectance	Sag resistance (relative humidity)	Low VOC
	SQ 600	2' x 2' x 5/8"	0.38	112	0.75	-	A	0.85	up to 100%	✓
	SQ 601	2' x 4' x 5/8"	0.38	112	0.75	-	A	0.85	up to 100%	✓
	SQ 609	20" x 60" x 3/4"	0.45	83.33	0.75	-	A	0.85	up to 100%	✓
	SQ 610	2' x 5' x 3/4"	0.45	100	0.75	-	A	0.85	up to 100%	✓
	SLN 620	2' x 2' x 5/8"	0.47	56	0.75	-	A	0.85	up to 100%	✓
	SLN 621	2' x 4' x 5/8"	0.47	112	0.75	-	A	0.85	up to 100%	✓
	SL 660	2' x 2' x 5/8"	0.47	56	0.75	-	A	0.85	up to 100%	✓
	SL 661	2' x 4' x 5/8"	0.47	112	0.75	-	A	0.85	up to 100%	✓


### 15/16" Suspension Systems

1200, 200 and Fire rated systems



### 9/16" Suspension Systems

4000, 4500, 4600 and Fire rated systems





### Material

Stone wool (Mineral Wool) ceiling tiles with factory painted glass scrim surface  
ASTM E1264 CLASSIFICATION: Type XX - Stone wool base with membrane-faced overlay, Pattern G



#### Fire Performance

Surface burning characteristics:  
UL723 (ASTM E84) Flame Spread Index: 0  
Smoke Developed Index (UL Labeled): 5  
CAN/ULC S102 Flame Spread Index: 5  
Smoke Developed Index: 0



#### Environment

Up to 37%  
recycled content



#### Thermal Insulation

R Value (BTU Units): 2.2 - 2.6  
RSI Value (Watts Units): 0.39 - 0.46



#### Sustainability

Many of Rockfon stone wool acoustic solutions are GREENGUARD Gold low VOC certified and meet the State of California's Department of Public Health Services Standard Practice for Specification Section 01350 (California Section 01350) for testing chemical emissions.

Selected potential applications: LEED, WELL, CHPS, Green Globes, BREEAM Int. and CALGreen.



#### Warranty Information

30-Year Limited  
Product Warranty.  
See [www.rockfon.com](http://www.rockfon.com)



#### Hygiene

Stone wool provides no  
sustenance to microorganisms



#### Cleaning

- Vacuum

Rockfon® is a registered trademark  
of the ROCKWOOL Group.

2019 | Subject to alterations in range and product technology without prior notice. Rockfon accepts no responsibility for printing errors.  
© ROCKWOOL International A/S 2018. All rights reserved. ® denotes a trademark that is registered in the United States of America.

052319

**Rockfon**

4849 S. Austin Ave.  
Chicago, IL 60638 USA

Tel. +1-800-323-7164  
Fax. +1-800-222-3744  
[www.rockfon.com](http://www.rockfon.com)

